

WASHDOWN STATIONS GENERAL SPECIFICATIONS

Chart for General Guidance in Choosing a Jet

Input Steam Pressure (PSI)	50	75	100	125	150		
Maximum Solution (PSI)	120	170	220	280	340		
						Jet Type	Steam Usage (lbs/hr)
Injector Capacity (GPM)	15	20	24	27	29	B1000	700-1500
	21	29	33	37	40	B1250	800-2000
	30	35	45	50	55	BX2000	1000-3000
	50	60	70	75	80	BX3000	1700-4500
	70	80	90	100	110	BX4000	2500-6000

Chart for General Guidance in Matching a Tank Cleaner with a Jet

Model Tankcleaner	Nozzle Size	Jet Type	Input PSI	Steam lbs./hr	Output PSI	Solution GPM
Drum Major	ALL	B1000	50-110	600-1200	50-150	15-25
2" Troll Ball		B1000	50-110	600-1200	50-150	15-25
		B1250	70-120	1000-1600	100-175	28-35
3" Troll Ball	ALL	BX2000	100-150	1200-3000	100-150	45-55
		BX3000	50-120	1500-3500	60-150	50-75
Hygienic 2 and 4		B1000	50-110	600-1200	50-150	12-20
Orbi-G3		B1000	50-110	600-1200	50-150	12-20
Orbi-G4		B1250	70-120	1000-1600	100-175	18-25
Tankmaster		B1000	70-120	600-1200	50-150	15-25
Jumbo	1/4"	BX3000	50-120	1500-3500	60-150	45-75
	5/16"	BX4000	50-125	2000-5000	50-150	60-100
	3/8"	BX4000	60-175	2500-6500	50-150	70-120
Tankman-Dual /Hygienic 80	3/8"	BX4000	60-125	2500-5000	100-200	70-100
Sellers 360-Dual 3/8"	3/8"	BX4000	60-125	2500-5000	100-200	70-100

Please note that the above chart is for general guidance only. Please refer to technical sections or factory for additional information.